



the most experienced name  
in high speed cameras

# MEMRECAM HX-6E

## High Speed Camera System

### The Memrecam HX series: the world's most versatile family of high speed camera systems!

#### FEATURES

CMOS Sensor: 2560 X 1920—  
all Active Pixels

Bit Depth: 12/10/8-bit  
(customer selectable)

Electronic Shutter:  
OPEN to < 1.1µsec

Variable Framing Profile:  
Test using a variety of frame  
rates, sequentially or in parallel.

Versatile Recording: Burst,  
multi-trigger, restart-trigger and  
image trigger.

A-EST Mode: High resolution  
timing and sync system to  
< 100 nanoseconds.

Straddle Mode:  
Inter-frame time for  
PIV applications equals  
250 nanoseconds.

Dual Segment Recording:  
Simultaneously record to two  
distinct memory segments at  
two different imaging speeds.

Ultra-High Light Sensitivity

Ruggedized for Range Use



NAC's Memrecam HX-6E offers an astounding 5 Mega Pixel resolution at up to 1,000 fps, Full HD resolution at up to 2,330 fps, 1 Mega Pixel resolution at up to 4,600 fps, and so much more! The HX-6E gives the user the best possible solutions: the highest resolutions available; the highest light sensitivity available; and ultra fast imaging.

### The HX-6E is literally two cameras in one!

*When it comes to reliable, high-quality, high-speed camera systems,  
make the proven choice with NAC and you'll see the visible difference!*



# MEMRECAM HX-6E

## High Speed Camera System



Memrecam HX-6E High Resolution Mode		
Max Res (pixels)	2560 X 1920	
Optical Format	35.20 mm	
fps @ Max Res	1,000	
	Mono	Color
ISO Rating	10,000	2,500

Memrecam HX-6E High Speed Mode		
Max Res (pixels)	1280 X 960	
Optical Format	35.20 mm	
fps @ Max Res	3,840	
	Mono	Color
ISO Rating	40,000	10,000

Memory Option	8GB, 16GB, 32GB	
Maximum fps	200,000	

Imaging Formats	Max fps @ Format
High Def: 16 X 9	
1920 X 1080	2,330
1280 X 720	5,110
Other Formats	
4 Mega Pixel	1,200
2 Mega Pixel	2,370
1 Mega Pixel	4,610
XGA (1024 X 768)	5,890
768 X 576	10,110
VGA (640 X 480)	14,150
512 X 512	16,200
512 X 384	21,500
320 X 320	37,170
320 X 240	52,900
320 X 192	65,350
320 X 96	123,440
320 X 48	200,000

\* Note: Recording Time Depends on Memory Configuration, Resolution, Frame Rate and Image Bit Depth.  
 Recording Time (seconds) = [(Memory Configuration X 1024 X 1,000,000) / (Resolution/Frame)] / (Frames/Second)  
 Resolution/Frame (Bytes) = (Horizontal pixels X Vertical Pixels X Bit Depth/8)

### NAC Image Technology

Memrecam High Speed Camera Systems also Feature:

- Auto Exposure Control
- Adjustable Frame Rates
- Automatic Temperature Calibration
- Continuously Adjustable Resolution
- Ultra-Fast Gig-E Interface with DataLock
- Fast Download to USB 2.0 HDD
- Continuous Live Video Output
- Remote & Local Control—(no PC required)
- Memory Backup
- DRES—Dynamic Range Expansion Shutter
- Multiple Trigger Modes
- Memory Segmentation
- External Sync Recording
- IRIG-B Capture & Sync with Phase Shift
- Compact, Rugged Design - 4.9kg  
110W x 140H x 333D(mm)



Visit our website at  
[www.nacinc.com](http://www.nacinc.com)

Please Note: Specifications described above are preliminary and subject to change.

11.01.12



#### Contact Us in the Americas:

NAC Image Technology  
 543 Country Club Drive, # B-534  
 Simi Valley, CA 93065  
 Tel: (800) 969-2711  
 E-mail: [sales@nacinc.com](mailto:sales@nacinc.com)

#### Contact Us in Europe:

NAC Deutschland GmbH  
 Hedelfingerstr. 54-70  
 70327 Stuttgart, Germany  
 Tel: +49(0)711 2201 885  
 E-mail: [rwestphal@nacinc.de](mailto:rwestphal@nacinc.de)

#### Contact Us in Asia:

NAC Image Technology Inc.  
 2-11-3 Kita-Aoama, Minato-ku  
 Tokyo 107-0061 Japan  
 Tel: +81 3 3796 7903  
 Email: [nacinternational@camnac.co.jp](mailto:nacinternational@camnac.co.jp)